



PERFIL (HSS)
ESTRUCTURAL

EN LARGOS DE 6.10 Y 12.2 METROS

A-500°B LIMITE ELASTICO 46,000 PSI (lb/in2)

DIMENSIONES EXTERIORES		ESPESOR		PESO	
PULGADA	mm.	PULGADA	mm.	Kg/m	
4" x 4"	102 x 102	.375	9.5	25.74	
6" x 6"	152 x 152	.187	4.7	21.72	
		.250	6.3	28.30	
		.312	7.9	34.75	
		.375	9.5	40.98	
		.500	12.7	52.46	
8" x 4"	203 x 102	.187	4.7	21.64	
		.250	6.3	28.36	
		.375	9.5	40.98	
		.500	12.7	52.45	
8" x 6"	203 x 152	.250	6.4	33.44	
		.375	9.5	48.52	
8" x 8"	203 x 203	.187	4.7	28.18	
		.250	6.3	38.52	
		.312	7.9	47.38	
		.375	9.5	56.07	
		.500	12.7	72.79	
10" x 10"	254 x 254	.187	4.7	36.89	
		.250	6.3	48.52	
		.312	7.9	60.16	
		.375	9.5	71.31	
		.500	12.7	92.95	
12" x 6"	305 x 152	.375	9.5	63.77	
12" x 8"	305 x 203	.375	9.5	71.31	
		.500	12.7	92.95	
12" x 12"	305 x 305	.250	6.3	58.69	
		.312	7.9	72.79	
		.375	9.5	86.56	
		.500	12.7	113.28	
		.625	15.9	138.80	
14" x 14"	356 x 356	.375	9.5	101.64	
		.500	12.7	133.44	
		.625	15.9	163.77	
16" x 16	406 x 406	.375	9.5	116.89	
		.500	12.7	153.77	
		.625	15.9	189.50	